

# VP5000

VHF · UHF (High & Low) · 700/800 MHz

P25 Phase 1 & 2 · Viking16

At just under 5.5 inches tall (140 mm), these small KENWOOD Viking portable radios are packed with advanced features for today's public safety agencies.

## Features

- Mixed protocol operation (P25 Phase 1 & 2 Trunking, P25 Conventional, Viking16, FM Analog)
- Mixed protocol zones (each channel in a zone can be from a different system)
- 1024 channels
- 1 Watt audio output for high noise environments
- Voice annunciation & custom announcement creation
- Fully ruggedized - IP67/IP68 & MIL-STD-810 C/D/E/F/G
- Full key models (w/numeric keypad) & standard key models (w/o numeric keypad)
- Built-In GPS receiver/antenna for enhanced awareness<sup>1</sup>
- MDC-1200 & GE-Star signaling
- P25 Authentication
- Bluetooth®
- Man Down
- Instant Recording Replay (IRR)
- Voice Recording
- Text Messaging
- Radio Cloning
- Bluetooth Low Energy
- Encryption
  - ARC4™ software encryption; compatible w/Motorola ADP™
  - DES-OFB
  - AES-256 (FIPS 140-2) Single and Multi-Key
  - Over-the-Air-Rekeying (OTAR)
  - VK5000 or Motorola KVL3000/KVL4000 Keyloader




## User Selectable Color Themes

- Multi-line text
- Multiple visual indicators including battery health & signal strength
- Day & night user selectable display options (8 themes available)



Day - High Contrast



Night - High Contrast

## Compatible With P25 Systems

- ATLAS® P25 Phase 1 and Phase 2 System
- Motorola Astro® 25 - P25 Phase 1 & Phase 2
- Harris VIDA® - P25 Phase 1 & Phase 2
- Airbus (formerly Cassidian) VESTA™ Radio - P25 Phase 1 & Phase 2

## Accessories

Complete line of accessories including microphones, speakers & antennas.

Download the accessory catalog at

<https://info.efjohnson.com/viking-accessory-catalog/>

We combine P25 design expertise with recognized quality & reliability along with advanced technology to make KENWOOD Viking radios simple to use & maintain.



### Perpetual Software Licensing

Adds greater value to your radios by extending the life of the software into your next hardware platform — you own the software option forever, and your licenses are simple to manage with our cloud-based tool — Vault™.



### Armada® Fleet Management

Update radios in a group rather than one at a time. One template programs both portables & mobiles. Supports either direct computer connection or Over-the-Air Programming (OTAP). Elite battery management enables wireless tracking of battery fleet.



### TrueVoice™ Noise Cancellation

Software-based noise cancellation automatically filters out noise source frequencies and eliminates the need for extra configuration. Works in analog or digital mode and with any accessory.

# VP5230/5330/5430 Portable Specifications

General		VP5230	VP5330	VP5430
Frequency Range		136-174 MHz (FCC ID K44431400)	Type 1: 450-520 MHz (FCC ID K44431500) Type 2: 380-470 MHz (FCC ID K44431501)	RX: 763-776, 851-870 MHz TX: 763-776, 793-806, 806-825, 851-870 MHz (FCC ID ALH442000)
Max. Channels Per Radio		1024		
Number of Zones		255		
Max. Channels Per Zone		255		
Channel Spacing	Analog	12.5/15/20/25*/30* kHz	12.5/25* kHz	12.5/25 kHz
	Digital	12.5 kHz	12.5 kHz	12.5 kHz
Power Supply		7.5 V DC $\pm$ 20%		
Operating Temperature		-22 °F to +140 °F (-30 °C to +60 °C)		
Frequency Stability [-22 °F to +140 °F (-30 °C to +60 °C), +77 °F Ref. (+25 °C)]		$\pm$ 1.0 ppm		
Dimensions (W x H x D) Projections Not Included	KNB-L2 (2,600 mAh)	2.28 x 5.47 x 1.56 in. (58.0 x 138.9 x 39.5 mm)		
	KNB-L3 (3,400 mAh)	2.28 x 5.47 x 1.77 in. (58.0 x 138.9 x 44.9 mm)		
Weight with Battery	KNB-L2 (2,600 mAh)	14.3 oz (406 g)		
	KNB-L3 (3,400 mAh)	15.8 oz (449 g)		
Receiver		VP5230	VP5330	VP5430
Sensitivity	P25 Digital (5% BER)	-119 dBm (0.025 $\mu$ V)		
	Analog (12 dB SINAD)	-119 dBm (0.025 $\mu$ V)		
Selectivity	P25 Digital	60 dB		
	Analog @ 12.5 kHz	65 dB		
	Analog @ 25 kHz	73 dB		
Intermodulation		73 dB	75 dB	
Spurious Rejection		80 dB	75 dB	
Audio Distortion		3%		
Audio Output Power		500 mW/8 $\Omega$ (3% Distortion)/1,000 mW/8 $\Omega$ (5% Distortion)		
Modulation		FM, C4FM, H-DQPSK		
Transmitter		VP5230	VP5330	VP5430
RF Output Power		1W/6W	1W/5W	1W/3W
Spurious Emission		-70 dB		
FM Hum & Noise	Analog @ 12.5 kHz	40 dB		
	Analog @ 25 kHz	45 dB		
Audio Distortion		2%		
Emission Designator		16K0F3E, 11K0F3E, 8K10F1E, 8K10F1D, 8K10F1W	16K0F3E, 14K0F3E, 11K0F3E, 8K10F1E, 8K10F1D, 8K10F1W	
Modulation		FM, C4FM, H-CPM		

Mil Standard	810G
Low Pressure	500.5/ I, II
High Temperature	501.5/ I, II
Low Temperature	502.5/ I, II
Temp. Shock	503.5/ I
Solar Radiation	505.5/ I
Rain	506.5/ I, III
Humidity	507.5/ II
Salt Fog	509.5
Dust	510.5/ I
Vibration	514.6/ I
Immersion	512.5/ I
Shock	516.6/ I, IV

Encryption Options	
Supported Encryption	AES, DES-OFB, ARC4
Encryption Key/ Radio	126 Common Key Reference (CKR), 126 Physical Identifier, (PID), Compatible w/ Motorola Key Variable Loader
Encryption Frame Re-sync Interval	P25 CAI 360 MSEC
Encryption Keying	External Key Loader, OTAR
Mode	OFB-Output Feedback
Encryption Type	Digital
Key Erasure	Keyboard Command
Standards	FIPS 46-3, FIPS 81, FIPS 140-2, FIPS 197

Hazardous Location Certification	
Certification Lab	CSA Group
Standard Applied	ANSI/TIA 4950-A-2014, UL913 5th Edition & ANSI/ISA-12.12.01-2011
Classification Rating	Intrinsically Safe: Classes I, II, III, Division 1, Groups D, E, F, G Non-incendive: Class I, Division 2, Groups A, B, C, D
Approved Battery	KNB-LS7
Approved Speaker Micro-phones	KMC-54WDM, KMC-70M
International Protection Standard	
Dust & Water	IP54, IP55
Immersion	IP67**/68***

\*Refer to the Viking VP5000 operating manual for detailed requirements & conditions for proper GPS operation.

\* 25/30 kHz in VHF/UHF Bands (except T-Band) are not included in the models sold in the USA or US territories.

\*\*IP67/68 - Must have the Speaker Mic Universal Connector or Universal Connector Protector connected.

\*\*\*IP68=1m/2H

Specifications shown are typical and subject to change without notice Please check the website for the latest version. V.09.25.21

© Copyright 2021 EF Johnson Technologies, Inc. (E.F. Johnson Company is operating entity) The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc.

**EF Johnson Technologies, Inc.**

a JVCKENWOOD Company

1440 Corporate Drive, Irving, TX 75038-2401

Phone: 800.328.3911 · efjohnson.com