## Project 25 Compliance Assessment Program SUPPLIER'S DECLARATION OF COMPLIANCE (SDOC) SDOC-EFJ-14070304 July 3, 2014

## **EF Johnson Technologies**

Standards and Regulatory Affairs 1440 Corporate Drive, Irving, TX 75038 Customer Contact: John Oblak Phone: 507-837-5116 Fax: 507-837-5120 http://www.efjohnson.com

joblak@efjohnson.com

Product Name: Viking VP900 VHF and 700/800 MHz Portable
Installed Options: Full and Limited Keypad, SEM Encryption Module Installed
Installed Vocoder: Enhanced Full Rate

Other Devices Tested With Viking VP900 Series Portable		
Manufacturer	Product Name, Definition, and Unique ID	Installed Options
Harris	P25 Trunked Infrastructure	System Release PR9D
Tait	TN9400 TaitNet P25 Network	Firmware 3.70, Kernel 3.60
EF Johnson	IP25 Trunked Infrastructure	Release 3.1-RC1
EF Johnson	Atlas Trunked Infrastructure	TSNI 1.0.5-1
Motorola	ASTRO Trunked Infrastructure	Release 25.7.14
Solutions		

EF Johnson Technologies hereby declares that Viking VP900 Series VHF and 700/800 MHz Portable products pass the test cases listed in the following Project 25 Compliance Assessment Bulletins in their entirety with exclusions as noted:

P25-CAB-CAI\_TEST\_REQ – March 2010, Section 2.1.1.1 – Project 25 Phase I Common Air Interface Conventional Subscriber Unit Performance, DTR-P25CAP081010-13110601.

P25-CAB-CAI\_TEST\_REQ – March 2010, Section 2.1.1.2 – Project 25 Phase I Common Air Interface Trunked Subscriber Unit Performance, DTR-P25CAP081010-13110601, and DTR-P25CAP081010-13020101.

P25-CAB-CAI\_TEST\_REQ – March 2010, Section 2.1.3.2 – Project 25 Phase I Common Air Interface Trunked Subscriber Unit Interoperability, DTR-TIMCO081016-VP600TN9400, DTR-P25CAP081010-12100801, DTR-P25CAP081017-1121211E01, DTR-P25CAP081010-13020401, and DTR-P25CAP081010-14070301. Test case 2.2.3.4.4 is not applicable for Harris P25, Motorola Solutions ASTRO, EF Johnson Technologies IP25, and EF Johnson Technologies Atlas infrastructures; see results of test case 2.2.3.4.3. Test case 2.2.3.4.3 is not applicable for TaitNet P25 infrastructure; see results of test case 2.2.3.4.4, Passed with the exception of test cases 2.2.3.4.5, and 2.2.3.4.6, when tested with EF Johnson Technologies IP25, EF Johnson Technologies Atlas, Motorola Solutions ASTRO, and TaitNet P25 trunking infrastructures, which are not supported in the infrastructures. Test cases for inter-system and inter-WACN roaming are not supported in the EF Johnson Viking VP900 portable nor infrastructures tested.

Summary Test Report Identification: STR-EFJ-14070304 issued on July 3, 2014.

July 3, 2014	John S. Oblak	
Issue date	Supplier's Authorized Representative Signature	
	John S. Oblak	
	Supplier's Authorized Representative Printed Name	

The information contained herein has been provided by the manufacturer of the product with permission to make the information publicly available. The Department of Homeland Security (DHS) is making this information available as a public service; however, DHS IS PROVIDING THE INFORMATION "AS IS". DHS MAKES NO EXPRESS OR IMPLIED WARRANTIES AND SPECIFICALLY, DHS MAKES NO WARRANTIES OF MERCHANTABILITY OR FITTNESS FOR A PARTICULAR PURPOSE, REGARDING THE ACCURACY OR USE OF THIS INFORMATION. Reference to any specific commercial products, processes, or services by trade name, trademark, manufacturer, or otherwise does not constitute an endorsement by or recommendation from DHS.

**OMB NO:** 1640-0015

**EXPIRATION DATE:** 07/31/2015

**Burden Statement** 

An agency may not consider or sponsor information collection and a person is not required to respond to this information collection unless it displays a current valid Office of Management and Budget control number and expiration date. The control number for this collection is 1640-0015 and this form will expire on 07/31/2015. The estimated average time to complete this form is 60 minutes per respondent. If you have any comments regarding the burden estimate you can write to Department of Homeland Security, Science and Technology Directorate, Washington, DC 20528.

DHS FORM 10044 - June 2009