Test Item Description	
Manufacturer	EF Johnson Technologies
Manufacturer Contact	John Oblak (507) 837-5116
Product Name	ATLAS 800 MHz Repeater
Installed Options	Trunking Software
Vocoder Identification	Not Applicable – The repeater does not incorporate a vocoder

Test Description

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.2.1.1 – Project 25 Phase 1 Common Air Interface Conventional Base Station/Repeater Performance

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.2.1.2 – Project 25 Phase 1 Common Air Interface Trunked Base Station/Repeater Performance

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.2.3.2 – Project 25 Phase 1 Common Air Interface Trunked Base station/Repeater Interoperability

Test Information	
P25 CAP Laboratory Code	P25CAP081010 (EF Johnson Technologies)
Date(s) of Test	January 28, 2013
Date of Issue	February 4, 2013

Test Information	
P25 CAP Laboratory Code	P25CAP081010 (EF Johnson Technologies)
Date(s) of Test	February 13, 2013 to February 25, 2013
Date of Issue	February 27, 2013

Test Information	
P25 CAP Laboratory Code P25CAP081010 (EF Johnson Technologies)	
Date(s) of Test	March 31, 2014
Date of Issue	April 1, 2014

Test Information	
P25 CAP Laboratory Code P25CAP081010 (EF Johnson Technologies)	
Date(s) of Test	March 28, 2014
Date of Issue	April 1, 2014

Test Information	
P25 CAP Laboratory Code	P25CAP081010 (EF Johnson Technologies)
Date(s) of Test	April 3, 2014
Date of Issue	April 4, 2014

Informative References	
Date	Title
March 2010	P25-CAB-CAI_TEST_REQ-March 2010

Other Devices Tested with ATLAS UHF Repeater		
Manufacturer	Product Name, Definition, and Unique ID	Installed Options
EF Johnson	Viking VP600 Series Portable	Firmware 8.2.12
Midland	STP-105B Portable Subscriber	Firmware 1.03.4646
Harris	P5400 Portable Subscriber	Firmware R02A26; DSP V18.2

P25-CAB-CAI_TEST_REQ - March 2010, Section 2.2.1.1 - Project 25 Phase 1 Common Air Interface Conventional Base Station/Repeater Performance

	Receive	er Tests	
Test Case	Description	Requirement	Results
2.1.4	Reference Sensitivity	≤ -116 dBm (Class A)	Р
2.1.5	Faded Reference Sensitivity	≤ -108 dBm (Class A)	Р
2.1.7	Adjacent Channel Rejection	≥ 60 dB (Class A)	Р
2.1.8	Co-Channel Rejection	≤ 9 dB	Р
2.1.9	Spurious Response Rejection	≥ 90 dB (Class A)	Р
2.1.10	Intermodulation Rejection	≥ 70 dB (Class B)	Р
2.1.11	Signal Displacement Bandwidth	≥ 1000 Hz	Р
2.1.17	Late Entry Unsquelch Delay		
	No Talk Group or Encryption	≤ 125 ms	N1
	Talk Group Only	≤ 370 ms	N1
	Encryption Only	≤ 370 ms	N1
	Both Talk Group and Encryption	≤ 460 ms	N1
2.1.18	Receiver Throughput Delay	≤ 125 ms	N1

P25-CAB-CAI_TEST_REQ - March 2010,
Section 2.2.1.1 - Project 25 Phase 1 Common
Air Interface Conventional Base
Station/Repeater Performance

Transmitter Tests			
Test Case	Description	Requirement	Results
2.2.8	Unwanted Emissions: Adjacent Channel Power Ratio	≥ 67 dB	Р
2.2.14	Transmitter Throughput Delay	≤ 125 ms	N2
2.2.15	Frequency Deviation for C4FM		
	High Level Signal Deviation	$2544 \; Hz < f_{dev} \le 3111 \; Hz$	Р
	Low Level Signal Deviation	$848~Hz < f_{dev} \leq 1037~Hz$	Р
2.2.16	Modulation Fidelity	≤ 5% (Class A)	Р
2.2.18	Transient Frequency Behavior		
	Time Interval t ₁ = 20 ms	∆f ≤ 12.5 kHz	Р
	Time Interval $t_2 = 50 \text{ ms}$	$ \Delta f \le 6.25 \text{ kHz}$	Р
	Time Interval t ₃ = 10 ms	∆f ≤ 12.5 kHz	Р

P25-CAB-CAI_TEST_REQ - March 2010,
Section 2.2.1.2 – Project 25 Phase 1 Common
Air Interface Trunked Base Station/Repeater
Performance

	Receiver Tests				
Test Case Description Requirement Results		Results			
2.1.4	Reference Sensitivity	≤ -116 dBm (Class A)	Р		
2.1.5	Faded Reference Sensitivity	≤ -108 dBm (Class A)	Р		
2.1.7	Adjacent Channel Rejection	≥ 60 dB (Class A)	Р		
2.1.8	Co-Channel Rejection	≤ 9 dB	Р		
2.1.9	Spurious Response Rejection	≥ 90 dB (Class A)	Р		
2.1.10	Intermodulation Rejection	≥ 70 dB (Class B)	Р		
2.1.11	Signal Displacement Bandwidth	≥ 1000 Hz	Р		

P25-CAB-CAI_TEST_REQ - March 2010,
Section 2.2.1.2 - Project 25 Phase 1 Common
Air Interface Trunked Base Station/Repeater
Performance

	Transmitter Tests				
Test Case	Test Case Description Requirement Results				
2.2.8	Unwanted Emissions: Adjacent Channel Power Ratio	≥ 67 dB	Р		
2.2.14	Transmitter Throughput Delay	≤ 125 ms	N2		
2.2.15	Frequency Deviation for C4FM High Level Signal Deviation Low Level Signal Deviation	$2544 \; Hz < f_{dev} \leq 3111 \; Hz$ $848 \; Hz < f_{dev} \leq 1037 \; Hz$	P P		
2.2.16	Modulation Fidelity	≤ 5% (Class A)	Р		
2.2.18	Transient Frequency Behavior Time Interval $t_1 = 20$ ms Time Interval $t_2 = 50$ ms Time Interval $t_3 = 10$ ms	$\begin{split} \Delta f &\leq 12.5 \text{ kHz} \\ \Delta f &\leq 6.25 \text{ kHz} \\ \Delta f &\leq 12.5 \text{ kHz} \end{split}$	Р Б		

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.2.1.2 – Project 25 Phase 1 Common Air Interface Trunked Base Station/Repeater Performance

	Trunking Infra	structure Tests	
Test Case	Description	Requirement Results	
2.3.3	Trunking Voice Access Time	500 ms	Р
		(Manufacturer Specified)	
2.3.4	Time to Grant		
	Non-Simulcast 37.5 ms ISP	Single TSBK < 337.5 ms	Р
		Double TSBK < 354.0 ms	N3
		Triple TSBK < 366.5 ms	N3
	Non-Simulcast 45 ms ISP	Single TSBK < 345.0 ms	Р
		Double TSBK < 361.5 ms	N3
		Triple TSBK < 374.0 ms	N3
	Simulcast 37.5 ms ISP	Single TSBK < 487.5 ms	N3
		Double TSBK < 504.0 ms	N3
		Triple TSBK < 516.5 ms	N3
	Simulcast 45 ms ISP	Single TSBK < 495.0 ms	N3
		Double TSBK < 511.5 ms	N3
		Triple TSBK < 524.0 ms	N3

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.2.3.2 – Project 25 Phase 1 Common Air Interface Trunked Base Station/Repeater Interoperability		DTR-P25CAP081010- 14040101	DTR-P25CAP081010- 14040102	DTR-P25CAP081010- 13020401
EF Johnson ATLAS Trunked Repeater		Midland STP-105B	Harris P5400	EF Johnson Viking VP600
Test Case	Description			
2.2.1	Full Registration			
2.2.1.4.1	Test Case 1 - Valid Registration			
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3
2.2.1.4.2	Test Case 2 – Denied or Refused Registration			
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3
2.2.1.4.3	Test Case 3 - Unverified Registration			
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3
2.2.2	Group Voice Call			
2.2.2.4.1	Test Case 1 – Group Call Granted		I	, , , , , , , , , , , , , , , , , , ,
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3
2.2.2.4.2	Test Case 2 – Group Call Denied		1	
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3
2.2.2.4.3	Test Case 3 – Group Call Request Queued		I	
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.2.3.2 – Project 25 Phase 1 Common Air Interface Trunked Base Station/Repeater Interoperability		DTR-P25CAP081010- 14040101	DTR-P25CAP081010- 14040102	DTR-P25CAP081010- 13020401
EF Johnson ATLAS Trunked Repeater		Midland STP-105B	Harris P5400	EF Johnson Viking VP600
Test Case	Description			
2.2.3	Unit-to-Unit Voice Call			
2.2.3.4.1	Test Case 1 – Unit-To-Unit Call With Target Availability Check			
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3
2.2.3.4.2	Test Case 2 – Unit-To-Unit Call Target Availability Check Denied By Target			
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3
2.2.3.4.3	Test Case 3 – Unit-To-Unit Call Queued With Target Availability Check – traffic channel assignment after target availability check			
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3
2.2.3.4.4	Test Case 4 – Unit-To-Unit Call Queued With Target Availability Check – traffic channel assignment before target availability check			
	Home Operation	N/A 1	N/A 1	N/A 1
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.2.3.2 – Project 25 Phase 1 Common Air Interface Trunked Base Station/Repeater Interoperability		DTR-P25CAP081010- 14040101	DTR-P25CAP081010- 14040102	DTR-P25CAP081010- 13020401
EF Johnson ATLAS Trunked Repeater		Midland STP-105B	Harris P5400	EF Johnson Viking VP600
Test Case	Description		I.	1
2.2.3	Unit-to-Unit Voice Call			
2.2.3.4.5	Test Case 5 – Unit-To-Unit Call Without Target Availability Check			
	Home Operation	N3	N3	N3
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3
2.2.3.4.6	Test Case 7 – Unit-To-Unit Call Queued Without Target Availability Check			
	Home Operation	N3	N3	N3
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3
2.2.3.4.7	Test Case 8 – Unit-To-Unit Call Denied			
	Home Operation	Р	Р	Р
	Home Operation Inter-System Operation	P N3	P N3	P N4

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.2.3.2 – Project 25 Phase 1 Common Air Interface Trunked Base Station/Repeater Interoperability		DTR-P25CAP081010- 14040101	DTR-P25CAP081010- 14040102	DTR-P25CAP081010- 13020401
EF Johnson ATLAS Trunked Repeater		Midland STP-105B	Harris P5400	EF Johnson Viking VP600
Test Case	Description			
2.2.4	Broadcast Voice Call			
2.2.4.4.1	Test Case 1 – Broadcast Voice Call		ı	ı
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3
2.2.5	Affiliation			
2.2.5.4.1	Test Case 1 - Radio Permitted To Affiliate With New Group		I	<u> </u>
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3
2.2.5.4.2	Test Case 2 - Radio Denied Affiliation To New Group		l	Ι
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3
2.2.6	Announcement Group Call			
2.2.6.4.1	Test Case 1 - Collection Of Talk Groups Receive Call		I	<u> </u>
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3
2.2.7	Emergency Alarm			
2.2.7.4.1	Test Case 1 - Emergency Alarm		ı	<u> </u>
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3

P25-CAB-CAI_TEST_REQ – March 2010, Section 2.2.3.2 – Project 25 Phase 1 Common Air Interface Trunked Base Station/Repeater Interoperability		DTR-P25CAP081010- 14040101	DTR-P25CAP081010- 14040102	DTR-P25CAP081010- 13020401
EF Johnson ATLAS Trunked Repeater			Harris P5400	EF Johnson Viking VP600
Test Case	Description			
2.2.8	Emergency Group Call			
2.2.8.4.1	Test Case 1 - Emergency Call			
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3
2.2.10	Encryption			
2.2.10.4.1	Test Case 1 - Call Privacy For Encrypted Call			
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3
2.2.11	Intra-Location Registration Area Roaming			
2.2.11.4.1	Test Case 1 – Idle Radio		ı	1
	Home Operation	Р	Р	Р
	Inter-System Operation	N3	N3	N3
	Inter-WACN Operation	N3	N3	N3

Model Class Definition	Applied to P25-CAB-CAI_Test_Req March 2010, 2.2.3.2		
Model Class Name	Product Name, Definition, and Unique ID	Installed Options	
ATLACILLE Deposter	ATLAS Trunked Repeater	Firmware: TSNI 1.0.5-1	
ATLAS UHF Repeater		Firmware: TSNI 1.2.0-14	

Test Case Result Definitions	
No Test Performed	
Test Does Not Apply to the Test Object	N/A
Test Object Meets Requirements	P (Pass)
Test Object Does Not Meet Requirements	F (Fail)
Test Object is Not Conclusive	I (Inconclusive)

Comments
N/A 1: Test cases 2.2.3.4.4 is not applicable for this base station/repeater; see results of test 2.2.3.4.3
N1: The receiver does not incorporate a vocoder.
N2: The transmitter does not incorporate a vocoder.
N3: The EF Johnson ATLAS TSNI infrastructure does not support this feature.

The information contained herein has been provided by the manufacturer of the product with permission to make the information publicly available. The Department of Homeland Security (DHS) is making this information available as a public service; however, DHS IS PROVIDING THE INFORMATION "AS IS". DHS MAKES NO EXPRESS OR IMPLIED WARRANTIES AND SPECIFICALLY, DHS MAKES NO WARRANTIES OF MERCHANTABILITY OR FITTNESS FOR A PARTICULAR PURPOSE, REGARDING THE ACCURACY OR USE OF THIS INFORMATION. Reference to any specific commercial products, processes, or services by trade name, trademark, manufacturer, or otherwise does not constitute an endorsement by or recommendation from DHS.

OMB NO: 1640-0015

EXPIRATION DATE: 07/31/2015

Burden Statement

An agency may not consider or sponsor information collection and a person is not required to respond to this information collection unless it displays a current valid Office of Management and Budget control number and expiration date. The control number for this collection is 1640-0015 and this form will expire on 07/31/2015. The estimated average time to complete this form is 60 minutes per respondent. If you have any comments regarding the burden estimate you can write to Department of Homeland Security, Science and Technology Directorate, Washington, DC 20528.

DHS FORM 10056 - June 2009